

## Declaration of Performance

No: 7-KBE70-U1,5-2

Intended use: **Premises for people to stay at the temperature below 16°C**

Manufacturer: **Maswerk Okna i Drzwi, ul. Batalionów Chłopskich 14, 83-000 Pruszcz Gdański**

Assessment and Verification of Constancy of Performance: **System 3**

Harmonised standard: **PN-EN 14351-1+A2:2016-10 October 2016**


Notified Body: **Mobilne Laboratorium Techniki Budowlanej Sp. z o.o., nr notyfikacji NB 2189**

Product-type	Single leaf windows	Multi leaf windows	Single leaf casement doors	Double leaf casement doors
Unique identification code of the product-type	O1-KBE70-U1,5	O2-KBE70-U1,5	D1-KBE70-U1,5	D2-KBE70-U1,5
Declared performance	Performance	Performance	Performance	Performance
Wind load resistance	npd.	C4	npd.	B2
Waterproofness – unshielded (A)	E1200	E900	E1200	E1050
Waterproofness – covered (B)	npd.	npd.	npd.	npd.
Security equipment capacity	threshold 350N	threshold 350N	threshold 350N	threshold 350N
Air permeability	Class 4	Class 4	Class 4	Class 4
Thermal conductance	<1,5 W/m <sup>2</sup> K	<1,5 W/m <sup>2</sup> K	<1,5 W/m <sup>2</sup> K	<1,5 W/m <sup>2</sup> K
Characteristics associated with the radiation	solar factor <b>0,64</b> light transmittance <b>0,82</b>	solar factor <b>0,64</b> light transmittance <b>0,82</b>	solar factor <b>0,64</b> light transmittance <b>0,82</b>	solar factor <b>0,64</b> light transmittance <b>0,82</b>
Acoustic properties	<b>32-35 dB</b>	<b>32-35 dB</b>	<b>32-35 dB</b>	<b>32-35 dB</b>
Dangerous substances	npd.	npd.	npd.	npd.

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued according to regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Pruszcz Gdański 01.01.2017r.

Sławomir Dyduch



.....  
(signature)